



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number: **0 687 103 A2**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **95303813.0**

(51) Int. Cl.⁶: **H04N 1/60**

(22) Date of filing: **05.06.95**

(30) Priority: **06.06.94 US 254629**

(43) Date of publication of application:
13.12.95 Bulletin 95/50

(84) Designated Contracting States:
DE FR GB

(71) Applicant: **XEROX CORPORATION**
Xerox Square
Rochester New York 14644 (US)

(72) Inventor: **Rolleston, Robert J.**
82 Clearview Drive
Penfield NY 14526 (US)
Inventor: **Maltz, Martin S.**
25 Dunrovin Lane
Rochester NY 14618 (US)

(74) Representative: **Reynolds, Julian David et al**
Rank Xerox Ltd
Patent Department
Parkway
Marlow Buckinghamshire SL7 1YL (GB)

(54) Color printer calibration with blended look up tables

(57) A color printer, responsive to printer signals to deposit printer colorants on a medium in accordance with printer signals received, is calibrated by operating the color printer with printer signals (C_p, M_p, Y_p, K_p) selected to cause the printer to print color samples on the medium; measuring (70) the color samples to determine a first colorimetric response of the printer to the printer signals using the first measured colorimetric response to generate a first mapping of colorimetric values (R_c, G_c, B_c) to printer signals; using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals; storing the first and additional mappings in a color conversion memory producing printer signals as a function of the first and additional mappings stored in the color conversion memory to convert color definitions from a first color space to the printer signals suitable for producing a corresponding response at the color printer.




FIG. 1

EP 0 687 103 A2

The present invention is directed towards compiling look up tables representative of printer characteristics, to enable the conversion of colors defined in a first color space to colors defined in a printer color space, and more particularly to a method of blending or combining the characteristics represented by such tables.

With a view to providing a full understanding of the present invention, reference is made to the following patents: US-A-4,500,919 for its teachings of a color conversion system converting information from RGB to CMYK; US-A-4,275,413 for its teachings of tetrahedral interpolation between first and second color spaces; and US-A-2,790,844 disclosing the desirability of defining an image in a first standard color space prior to conversion of the image coordinates to a second printer based coordinate system. Reference is also made to the following articles: Po-Chieh Hung, "Tetrahedral Division Technique Applied to Colorimetric Calibration for Imaging Media", Annual Meeting IS&T, NJ, May, 1992, pp. 419-422; and Sigfredo I. Nin, et al., "Printing CIELAB Images on a CMYK Printer Using Tri-Linear Interpolation", SPIE Proceedings, Vol. 1670, 1992, pp. 316-324; and William J. Gordon et al., "Shepard's Method of 'Metric Interpolation' applied to Bivariate and Multivariate Interpolation", Mathematics of Computation, Vol. 32, No. 141, January 1978, pp. 253-264 and P. Lancaster et al., "Surfaces Generated by Moving Least Squares Methods", Mathematics of Computation, Vol. 32, No. 155, July 1981, pp. 141-158; and Pekka Laihanen, "Colour Reproduction Theory Based on the Principles of Colour Science", Advances in Printing Science and Technology, W. H. Banks ed., Pentech Press, London, 1988, pp. 1-36; and Pekka Laihanen, "Optimization of Digital Color Reproduction on the Basis of Visual Assessment of Reproduced Images", Proceedings of the SID, Vol 30, No. 3, 1989, pp. 183-190.

The generation of color documents can be thought of as a two step process: first, the generation of the image by means of scanning an original document with a color image input terminal or scanner or, alternatively, creating a color image on a work station operated in accordance with a color image creation program; and secondly, printing of that image with a color printer in accordance with the colors defined by the scanner or computer generated image. Scanner output is commonly transformed to a color space of tristimulus values, i.e., RGB (red-green-blue). Commonly, these values are a linear transformation of the standard XYZ coordinates of CIE color space, or a corrected transform of those values. In the case of computer generated images, colors defined by the user at the user interface of a workstation can be defined initially in color space of tristimulus values. These colors are defined independently of any particular device, and accordingly reference is made to the information as being "device independent".

Printers commonly have an output which can be defined as existing in a color space called CMYK (cyan-magenta-yellow-key or black) which is uniquely defined for the printer by its capabilities and colorants. Printers operate by the addition of multiple layers of ink or colorant in layers to a page. The response of the printer tends to be relatively non-linear. These colors are defined for a particular device, and accordingly reference is made to the information as being "device dependent". Thus, while a printer receives information in a device independent color space, it must convert that information to print in a device dependent color space, which reflects the gamut or possible range of colors of the printer. Printers may print with colors beyond CMYK, for a variety of special purposes or to extend the device gamut.

The desirability of operating in a device independent color space with subsequent conversion to a device dependent color space is well known, as shown by US-A-4,500,919 and US-A-2,790,844, and US-A-4,275,413. There are many methods of conversion between color spaces, all of which begin with the measurement of printer response to certain input values. Commonly, a printer is driven with a set of input values reflecting color samples throughout the printer gamut, the color samples are printed in normal operation of the printer. As previously noted, most printers have non-linear response characteristics.

In US-A-4,275,413, the information derived is placed into look up tables, stored in a memory, perhaps ROM memory or RAM memory where the look up table relates input color space to output color space. The look up table is commonly a three dimensional table since color is defined with three variables. In RGB space, at a scanner or computer, space can be defined as three dimensional with black at the origin of a three dimensional coordinate system 0, 0, 0, and white at the maximum of a three dimensional coordinate system which an 8-bit system, would be located at 255, 255, 255. Each of the three axes radiating from the origin point therefore respectively define red, green, and blue. In the 8-bit system suggested, there will be, however, over 16 million possible colors (256^3). There are clearly too many values for a 1:1 mapping of RGB to CMY. Therefore, the look up tables consist of a set of values which could be said to be the intersections for corners of a set of cubes mounted on top of one another. Colors falling within each cubic volume can be interpolated from the measured values, through many methods including tri-linear interpolation, tetrahedral interpolation, polynomial interpolation, linear interpolation, and any other interpolation method depending on the desired accuracy of the result.

It would be very easy to index device dependent color values or specifications to device independent color specifications, but that is not the requirement. Instead, device independent specifications must be

mapped to device dependent specifications. Several problems arise. Of course, the primary problem is that the printer response is not a linear response. A second problem is that the color space, and therefore the coordinates defined in the color space must be maintained as a uniform grid for maximum efficiency of some interpolation methods.

Accordingly, a multi-dimensional look up table (LUT) may be constructed which puts device independent input values into a predictable grid pattern. One method of accomplishing this requirement is by an interpolation process which derives a value at a desired location as a function of all (or a significant set) of measured color values. This method of interpolation is known as Shepard's Method (see, for example "Shepard's Method of 'Metric Interpolation' to Bivariate and Multivariate Interpolation" by W. Gordon and J. Wixom, *Mathematics of Computation*, Vol. 32, No. 141, January 1978, pp. 253-264). Shepard's Method suggests that a vector can be thought of as defining the difference between an asked-for color which was directed to a printer in the printed color. Then, for any other point in color space which is desired, that point can be thought of as a vector quantity, derived by averaging over the space all the vectors, each vector weighted by a function which decreases its effect on the vector as that vector is further and further away from the point coloring question. In one useful formula, each vector is weighted by a function of $1/d^4$.

Alternatively the method of Po-Chieh Hung, "Colorimetric Calibration for Scanners and Media", SPIE, Vol. 1448, Camera and Input Scanner System, (1991), describes a method of inverse tetrahedral interpolation, to the same effect as the described Shepard's Method.

In one actual calibration test, it was noted that the weighted averaging technique produced a table which gave good color reproduction in one region of color space (the light colors), but not in another (the dark colors). The tetrahedral inversion technique was just the complement of this, i.e., it gave good color reproduction where the weighted average technique did not (the dark colors), and gave poorer color reproduction of colors where the weighted average technique gave good color reproduction (the light colors).

Similar to the above problem, it has been noted that often, after a change in process parameters due to time, change of materials, refilling toner, etc., a change in calibration is required only in a portion of the overall color gamut of a printer. Recalibration of the entire space is costly in terms of processing time. It would be desirable to only recalibrate a portion of the color space, or alternatively, to use the best portions of the color space mapping.

The references cited herein are incorporated by reference for their teachings.

In accordance with the invention there is provided

a method of calibrating a color printer, the color printer responsive to printer signals to deposit printer colorants on a medium in accordance with printer signals received, including the steps of: operating the color printer with printer signals selected to cause the printer to print color samples on the medium; measuring the color samples to determine a first colorimetric response of the printer to the printer signals; using the first measured colorimetric response to generate a first mapping of colorimetric signals to printer signals; using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals; storing the first and additional mappings in a color conversion memory; producing printer signals as a function of the first and additional mappings stored in the color conversion memory to convert color signals from a first color space to the printer signals suitable for producing a corresponding response at the color printer.

In accordance with one aspect of the invention, the selected areas or portions of two (or more) look up tables mapping colorimetric values to color printer responses are blended. The output response for any colorimetric description from the blended tables is a linear combination of the output responses of the separate tables, where the linear function is adjusted as a function of position of the colorimetric description within colorimetric color space.

In accordance with another aspect of the invention, the second look up table may differ from the first look up table due to the creation method although using the same set of color samples, or the second look up table may differ from the first look up table due to using a different set of color samples.

The invention further provides a colour printer according to claims 3 and 4 of the appended claims.

The invention further provides a programmable printing apparatus when suitably programmed for carrying out the method of any of the appended claims or any of the particular embodiments described herein.

These and other aspects of the invention will become apparent from the following descriptions used to illustrate a preferred embodiment of the invention read in conjunction with the accompanying drawings in which:

Figures 1 and 2 together illustrate an overall system block diagram showing a color printing system in which the present invention might find use; and
Figure 3 illustrates the blended mapping described.

Referring now to the drawings where the showings are for the purpose of describing an embodiment of the invention and not for limiting same, a basic system for carrying out the present invention is shown in Figure 1. In a system, a scanner 10, such as perhaps

the color scanner available in the Xerox 5775 digital color copiers, which can be calibrated to produce a set of digital colorimetric or device independent data describing an original image 12, rendered in colors R_o , G_o , B_o , which, by definition, can be defined in terms of a colorimetric rgb space. Resulting from the scanning operation is a set of scanner image signals R_s , G_s , B_s , defined in device dependent scanner terms. Incorporated into the scanner or another processing path is a post-scanning processor 14, which provides correction of scanner image signals R_s , G_s , B_s to colorimetric terms, R_c , G_c , B_c , typically digital in nature. The values may be in terms of CIE color space (rgb), or the $L^*a^*b^*$, or luminance-chrominance space (LC, C_2). A color space transform, indicated by block 20, such as that described in US-A-4,275,413 to Sakamoto, is used to convert the device independent data to device dependent data. The output of color space transform 20 is the image defined in terms of a device dependent space, or printer colorant signals C_p , M_p , Y_p , K_p that will be used to drive a printer 30. In one possible example, the colorant signals represent the relative amounts of cyan, magenta, yellow, and black toners to be deposited over a given area in an electrophotographic printer, such as, again, Xerox 5775 digital color copier. The printed output image may be said to be defined in terms of R_p , G_p , B_p , which are hoped to have a relationship with R_c , G_c , B_c such that the printed output image has a color that is colorimetrically similar to the original image, although that similarity is ultimately dependent upon the gamut of the printing device.

With reference now to Figure 2, and color space transformation and color correction 20, initially, R_c , G_c , B_c color signals are directed to a lookup table and interpolation device 40, which provides a three dimensional look up arrangement in a device memory such as a RAM or other addressable memory device, which will meet speed and memory requirements for a particular device. Color signals R_c , G_c , B_c are processed to generate address entries to a table therein which stores a set of transform coefficients with which the signals R_c , G_c , B_c may be processed to convert them to C_x , M_x , Y_x colorant signals or any multi-dimensional output color space including but not limited to CMYK or spectral data. Values which are not mapped may be determined through interpolation. As described in US-A-5,305,119, entitled "Color Printer Calibration Architecture", black addition for under color removal and gray balance processing may also be combined into the color space transform element. Although these features are not required, they are desirable and are illustrated herein. When we refer to colorimetric spaces, we are referring to spaces which are transforms of CIE XYZ space (1931). When we refer to device dependent space, we refer to a color space which is defined only in terms of operation of the device using it. While many color spaces have

three dimensions, it is possible to have color spaces with less than three dimensions or more than three dimensions, and likewise, it is possible for printers to use less than three colorants or more than four colorants.

It will no doubt be recognized that there are many methods of providing a transform from device independent data to device dependent data, with US-A-4,275,413 describing one method, which itself can be varied. Once a conversion table is established, a method of interpolation referred to as tri-linear or cubic interpolation may also be used to calculate output values from the limited set of input values.

To create the table, a set of color patches are created, preferably including determined linearization and black addition. This is done by printing and measuring about 1000 to 4000 patches of printer colors distributed throughout the color space, i.e., a large set of printer driving signals are generated, in varying densities of combinations of C, M, Y, K , or other printer colors and used to drive the printer. The color of each patch is measured, using a spectrophotometer to determine color in terms of R_c, B_c, G_c . The measured colors of these patches are used to build a multi-dimensional look up table (LUT) relating R_c, B_c, G_c defined colors to $C_x M_x Y_x$ defined colors. Conversions that do not include mapped and measured points may be interpolated or extrapolated. Reference is made to EP-A-000,000, corresponding to United States Patent Application No. 08/144,987 to Rolleston entitled, "Color Printer Calibration Test Pattern", filed October 29, 1993, which shows and describes a calibration test pattern for this purpose.

With reference again to Figure 1, a calibration image is conveniently stored in a device memory such as calibration ROM 60, RAM, floppy or the like, or generated on the fly with a predetermined generation function. Signals stored therein are directed to the printer under the control of printer controller 65. Densitometer, spectrophotometer or colorimetrically corrected scanner 70 is used to scan the calibration target and produce R_c , G_c , B_c signal values as a function of sensed density, representing the colors of each scanned patch. Interpatch correlation processor 80 reads the responses provided from densitometer 70 for each location in the calibration target and correlates the response with the input colorant signals, so that an $R_c G_c B_c$ to colorant mapping is generated.

The device independent values may be mapped to the device dependent space, perhaps in a manner described by Po-Chieh Hung, in "Colorimetric Calibration for Scanners and Media", SPIE, Vol. 1448, Camera and Input Scanner System, (1991).

With the look up table derived, it may be stored in LUT and interpolation 40, for use in converting device dependent values received from image creators to device independent printer signals.

In accordance with the invention, if for any reason

a second set of mappings of colorimetric values to printer signals is generated, it immediately becomes apparent that one set may be better than the other set. More likely however, is that one set is better than the other set for only a portion of color space. Thus, a desire for optimum reproduction would require that both sets of data be used.

Accordingly, and with reference to Figure 3, within LUT and Interpolation 40 are multiple look up tables, including a weight table 100, and look up tables LUT1 ... LUTN, numbered 102. Conveniently, these tables are in a format that provides the colorimetric color description R_C , G_C , B_C as an index or input value to each table. Coefficient table 100 has as outputs coefficients A_1 ... A_N . Each coefficient A_1 ... A_N is derivable as a function of the position of the colorimetric color description in color space, and varies with the relative weight to be accorded to the LUT's relationship that region or portion of color space. In one embodiment, there is a set of coefficients A_1 ... A_N corresponding to each table LUT1 ... LUTN. Values are stored to coefficient table 100 and LUT1 ... LUTN from LUT processor 100. Coefficients stored to coefficient table 100 may also be operator or user generated and input to coefficient table 100 from a user interface.

LUT1 ... LUTN are tables derived through the processes described above for the generation of first color space to second color space conversion. They are also in a format that provides the colorimetric color description R_C , G_C , B_C as an index or input value to each table, but provide, for example, output CMYK signals. The signals are from LUT output respectively to multipliers 120_1 ... 120_N which have as a second input a corresponding coefficient A_1 ... A_N from Table 100. The output of multipliers 120_1 ... 120_N is directed to an adder or accumulator 130 which actually adds the results together and directs its output to another area in memory, LUT_{NEW} 134. From this area in memory, interpolator 140 can receive the stored information to produce its color conversion values. Interpolator 140, using for example trilinear or tetrahedral interpolation (as taught for example in US-A-4,275,413) uses the stored LUT values to derive interpolated output values. (Figure 3 shows block 40 from Figure 1, labeled LUT AND INTERPOLATION, and therefore should include the tetrahedral or trilinear interpolation function, which is represented by interpolator 140.)

It can therefore be seen that the plural table blending function is characterized by

$$\text{LUT}_{\text{NEW}}(r,g,b) = A_1(r,g,b) \times \text{LUT}_1(r,g,b) + A_2(r,g,b) \times \text{LUT}_2(r,g,b) + A_3(r,g,b) \times \text{LUT}_3(r,g,b) + \dots + A_N(r,g,b) \times \text{LUT}_N(r,g,b)$$

such that

$$A_1(r,g,b) + A_2(r,g,b) + A_3(r,g,b) + \dots + A_N(r,g,b) = 1$$

at each location in color space.

It is interesting to note that the case of only two

tables, LUT1 and LUT 2 (which is expected to be a common case), can be addressed in a special manner, since if weight $A_1 = A$ is accorded to LUT1, the weight A_2 for LUT 2 is equal $1-A$, and accordingly need not be stored independently. The special case of two LUT's can be addressed as:

$$\text{LUT}_{\text{NEW}}(r,g,b) = A(r,g,b) \times \text{LUT}_1(r,g,b) + [1 - A(r,g,b)] \times \text{LUT}_2(r,g,b)$$

where LUT1() and LUT2() are the values of the first and second LUT's at some location (i.e. r, g, b) in the table, and $A()$ is a function of the table location such that $0 \leq A \leq 1$. Of course, this result can be generalized to include N tables with N-1 weights.

In considering the function of position, it is useful to note that the function need not be a linear combination of LUT's. A particularly valuable function may represent use of only a single LUT at any point in space. Thus, within the area best characterized by LUT N, $A_N = 1$, while all other LUT's have a value of $A = 0$.

The embodiment described has been illustrated as generating a new LUT, named LUT_{NEW}. However, it is within the scope of the invention to generate blended values from LUT1 ... LUTN on the fly, without storage or creation of a new LUT. Thus, the output of adder 130 would be directed immediately to interpolator 140, for each value of $R_C G_C B_C$ which is directed to coefficient table 100 and LUT table 102.

It is worth noting that the blending can be performed in any color space or coordinate system, and that the idea is not limited to using a linear combination of the preliminary LUTs. The novel aspect of this invention is the ability to combine several different LUTs into a single LUT. This technique has been reduced to practice, and in the example sighted above, the weights were set such that $A = 1$ at R, G, B, C, M, Y and W (i.e., all colors including white), and $A = 0$ at K (black). Intermediate values of A were calculated by interpolation within this cube. LUT1 was the LUT which resulted from using a weighted average, and LUT2 was obtained by using tetrahedral inversion.

It will no doubt be appreciated that while we have shown the use of the invention in the conversion of a device independent color space to a device dependent color space, the invention applies equally as well to conversions to any transformation from a first space to a second space, irrespective of the nature of the space as device dependent or not.

It will no doubt be appreciated that the present invention can be accomplished through application software accomplishing the described functions, though a hardware circuit, which will probably provide optimum speed, or through some combination of software and hardware.

Claims

1. A method of calibrating a color printer, the color printer responsive to printer signals to deposit printer colorants on a medium in accordance with printer signals received, including the steps of:
 - operating the color printer with printer signals selected to cause the printer to print color samples on the medium;
 - measuring the color samples to determine a first colorimetric response of the printer to the printer signals;
 - using the first measured colorimetric response to generate a first mapping of colorimetric signals to printer signals;
 - using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals;
 - storing the first and additional mappings in a color conversion memory;
 - producing printer signals as a function of the first and additional mappings stored in the color conversion memory to convert color signals from a first color space to the printer signals suitable for producing a corresponding response at the color printer.
2. A method of calibrating a color printer, the color printer responsive to printer signals to deposit printer colorants on a medium in accordance with printer signals received, including the steps of:
 - operating the color printer with printer signals selected to cause the printer to print color samples on the medium;
 - measuring the color samples to determine a first colorimetric response of the printer to the printer signals;
 - using the first measured colorimetric response to generate a first mapping of colorimetric values to printer signals;
 - using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals;
 - generating a color conversion mapping as a function of the first and additional mappings and storing said mapping in a color conversion memory;
 - producing printer signals as a function of the color conversion mapping stored in the color conversion memory to convert color signals from a first color space to printer signals suitable for producing a corresponding response at the color printer.
3. A color printer including a calibration system, the color printer responsive to printer signals directed thereto to deposit printer colorants on a medium in accordance with printer signals received, comprising:
 - means for generating printer signals selected to cause the printer to print color samples on the medium;
 - means for measuring a first colorimetric response of the printer to the printer signals from the color samples;
 - means for using the first measured colorimetric response to generate a mapping of colorimetric values to printer signals;
 - means for using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals;
 - a color conversion memory;
 - printer control means for storing the first and additional mappings in the color conversion memory;
 - weighting means to producing printer signals as a function of the first and additional mappings stored in the color conversion memory, to convert color definitions from a first color space to printer signals suitable for producing a corresponding response at the color printer.
4. A color printer including a calibration system, the color printer responsive to printer signals directed thereto to deposit printer colorants on a medium in accordance with printer signals received, comprising:
 - means for generating printer signals selected to cause the printer to print color samples on the medium;
 - means for measuring a first colorimetric response of the printer to the printer signals from the color samples;
 - means for using the first measured colorimetric response to generate a mapping of colorimetric values to printer signals;
 - means for using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals;
 - a color conversion memory;
 - means for combining at least the first measured colorimetric response and any subsequent measured colorimetric response to produce a color conversion mapping, and storing said color conversion mapping in said color conversion memory;
 - weighting means to producing printer signals as a function of the first and additional mappings stored in the color conversion memory, to convert color definitions from a first color space

to printer signals suitable for producing a corresponding response at the color printer.

values received to printer signals.

5. A method or device as described in any of claims 1 to 4, wherein said colorimetric signals are red, green and blue signals. 5
6. A method or device as described in any of the preceding claims, wherein said printer signals correspond to (A) printing cyan, magenta and yellow colorants, (B) printing cyan, magenta, yellow and black colorants, (C) printing cyan, magenta, yellow and at least one additional different non-black colorant or (D) printing cyan, magenta, yellow, black and at least one additional different colorant. 10 15
7. A method or device as described in any of the preceding claims, wherein the step of producing printer signals as a function of the first and additional mappings stored in the color conversion memory does so in accordance with the function:

$$C, M, Y = A1(r, g, b) \times LUT1(r, g, b) + A2(r, g, b) \times LUT2(r, g, b) + A3(r, g, b) \times LUT3(r, g, b) + \dots + AN(r, g, b) \times LUTN(r, g, b)$$
 where C, M, Y is the printer signal produced as a function of the first and additional mappings stored in the color conversion memory, AN is a color space location dependent weight and LUTN(r, g, b) is the first and additional mappings of colorimetric values to printer signals. 20 25 30
8. A method or device as described in claim 7, wherein

$$A1 + A2 + A3 \dots + AN = 1.$$
 35
9. A method or device as described in claim 7 or 8, where a single member of the set {A1, A2 + A3... + AN} is equal to 1, and the remaining member of the set are equal to 0 at any location in location in color space. 40
10. A method of calibrating a color printer responsive to printer signals to deposit printer colorants on a medium in accordance with printer signals received, including the steps of: 45
 - producing a calibration print as a printer response sample;
 - deriving a first mapping relating colorimetric values to printer response; 50
 - deriving at least one additional mapping relating colorimetric values to printer response;
 - generating a color conversion mapping as a function of the first and additional mappings and storing said mapping in a color conversion memory; 55
 - operating the calibrated printer with the color conversion mapping to convert colorimetric




FIG. 1






FIG. 2

FIG. 3





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 687 103 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
03.01.1996 Bulletin 1996/01

(51) Int Cl.⁶: H04N 1/60

(43) Date of publication A2:
13.12.1995 Bulletin 1995/50

(21) Application number: 95303813.0

(22) Date of filing: 05.06.1995

(84) Designated Contracting States:
DE FR GB

(30) Priority: 06.06.1994 US 254629

(71) Applicant: XEROX CORPORATION
Rochester, New York 14644 (US)

(72) Inventors:

- Rolleston, Robert J.
Penfield NY 14526 (US)
- Maltz, Martin S.
Rochester NY 14618 (US)

(74) Representative: Reynolds, Julian David et al
Marlow, Buckinghamshire SL7 1YL (GB)

(54) Color printer calibration with blended look up tables

(57) A color printer, responsive to printer signals to deposit printer colorants on a medium in accordance with printer signals received, is calibrated by operating the color printer with printer signals (C_p, M_p, Y_p, K_p) selected to cause the printer to print color samples on the medium; measuring (70) the color samples to determine a first colorimetric response of the printer to the printer signals using the first measured colorimetric response to generate a first mapping of colorimetric values (R_c, G_c, B_c) to printer signals; using the first measured colorimetric response or a subsequent measured colorimetric response to generate at least one additional mapping of colorimetric values to printer signals; storing the first and additional mappings in a color conversion memory producing printer signals as a function of the first and additional mappings stored in the color conversion memory to convert color definitions from a first color space to the printer signals suitable for producing a corresponding response at the color printer.




FIG. 1

EP 0 687 103 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 95 30 3813

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X Y	EP-A-0 398 502 (HEWLETTE-PACKARD COMPANY) * abstract; figures 1-6 * * column 5, line 2 - column 8, line 2 * ---	1-6,10 7,8	H04N1/60
Y A	EP-A-0 273 398 (KONICA) * abstract; figures 2,27-37 * * page 11, line 32 - line 55 * * page 13, line 57 - page 14, line 19 * * page 18, line 28 - line 35 * ---	7,8 9	
A	US-A-5 262 833 (FUKUSHIMA ET AL.) * abstract; figures 5,6,13,14 * * figures 17-22 * ---	1-6,10	
A	WO-A-91 02427 (EASTMAN KODAK) * abstract; figures 1-9 * * page 5, line 5 - line 25 * ---	1-6,20	
A	US-A-5 289 295 (YUMIBA ET AL.) * abstract; figures 1-20 * -----	1-6,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 October 1995	Examiner Kassow, H
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1501 03/82 (P04C01)